TECASAFE® Ecogreen





TECASAFE® ECOGREEN XL 9200 – 200 g/m²

GUARANTEED COMFORT IN ANY SITUATION

Soft, silky natural fibres provide superior moisture management, keeping you comfortable, cool and dry at all times thanks to advanced breathability.

LASTING LOOKS EVEN WITH FREQUENT WASHING

High durability maximises the lifetime of your protective workwear, with an excellent colour fastness rating of 4-5 after 50 industrial washing cycles (ISO 15797).

FIRST ECO-FRIENDLY INHERENT FR FABRIC WITH CLOSE TO 50% SUSTAINABLE MATERIALS

Lowers your footprint without compromising on the best inherent FR multi-norm performance. Featuring sustainably-sourced eco-friendly TENCEL™ Lyocell.



TECASAFE® Ecogreen



TECHNICAL DATA	TECACACES FOOGREEN	TECTMETHOD
TECHNICAL DATA	TECASAFE® ECOGREEN	TEST METHOD
Quality	XL 9200	
Width	150 cm (+2/-1 cm)	ISO 3801: 1978
Weight	200 g/m² (± 5%)	ISO 3932: 1980
Composition	Modacrylic/TENCEL [™] Lyocell/ para-aramid/Static-Control [™]	
Construction	2/1 twill	
Available finishes	Standard: Comfort. Optional: Hydro-Tec	
Physical performance		
Tensile strength	750 N x 500 N (± 10%)	ISO 13934-1: 1999
Care labelling		
Domestic laundering	FOT X O P	
Industrial laundering	75 °C Colour: White:	
PPE requirements*		

Copyright symbols: NEN, Delft (Netherlands)

CERTIFICATION		
©	Industrial flame & heat hazards	EN ISO 11612 A1,A2,B1,C1, E1, F1: 2015 (A1 + A2= 100 x ISO 15797 - 75 °C)
NEPA	Short-duration thermal exposures from fire	NFPA 2112: 2018
	Electric Arc	Single Layer: EN IEC 61482-1-2, class 1; 2015 HRC/Category 1 (4 ≤ATPV ≥ 8 cal/cm²) System: XL9200 + XL9240 EN IEC 61482-1-2; 2015 class 2 (7kA) System: HRC/Category 2 (8 ≤ATPV ≥ 25 cal/cm²)
<u>F</u>	Anti-Static for explosion risk	EN 1149-5: 2018, EN 1149-3: 2004
	Liquid chemicals**	EN 13034: 2005 + A1: 2009
(\textit{\textbf{\textit{\textbf{\t	High Visibility colour. Contrast colours: Delftblue 89249 and Twilight 89250	EN ISO 20471: 2013
	General requirements***	EN ISO 13688: 2013
	Öko-Tex Standard 100, class 2	Centexbel, no. 0903009

^{**} Hydro-Tec finish only

*** Tested on specific colours

COLOURS





TENCATE PATENTED

Member of the E.T.S.A.





This fabric is an UL certified product:





All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TenCate Protective Fabrics Europe declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.